



QUAILITY
CHANGES THE WORLD

Vertical Reach: 36.5m

SYG5231THBCZ 370C-8 / 370C-8(R) TRUCK-MOUNTED CONCRETE PUMP

Energy-saving

With cycle times of up to 29 per minute (at 12MPa), pumpefficiency is increased up to 25% while fuel consumption is decreased by up to 10%.

Highly Wear Resistant Parts

The highly wear resistant parts improve efficiency and reduce down time.

Safety

Our C8 series truck mounted concrete pump exemplifies Sany's precise, rigorous manufacturing philosophy and uncompromising focus on safety.

Self-diagnosis Technology

Continually monitors more than 200 aspects of the system during operation. Faults are displayed on the monitor. Review of the detected faults can reduce troubleshooting time by 70%.

TECHNICAL SPECIFICATIONS

Model			SYG5231THBCZ 370C-8	SYG5231THBCZ 370C-8(R)
Overall Specification	Length(mm)		10120	10120
	Width(mm)		2530	2530
	Height(mm)		3850	3850
	Dead Weight(kg)		23000	23000
Boom & Outrigger Specification	Vertical Reach(m)		36.5	36.5
	Horizontal Reach(m)		31.8	31.8
	Reach Depth(m)		20.9	20.9
	Min. Unfolded Reach(m)		7.5	7.5
	1st Section	Length(mm)	7550	7550
		Articulation(°)	89	89
	2nd Section	Length(mm)	6025	6025
		Articulation(°)	180	180
	3rd Section	Length(mm)	5835	5835
		Articulation(°)	180	180
	4th Section	Length(mm)	6660	6660
		Articulation(°)	230	230
	5th Section	Length(mm)	6355	6355
		Articulation(°)	180	180
	Rotation(°)		±360°	±360°
	Front Outrigger Spread L-R(mm)		6110	6110
	Rear Outrigger Spread L-R(mm)		8500	8500
Pumping Systerm Specification	Output (m³/h)	Low-Pressure	120	120
		High-Pressure	70	70
	Pressure (MPa)	Low-Pressure	8	8
		High-Pressure	13	13
	Delivery Cylinder Diameter(mm)		230	230
	Stroke Length(mm)		1600	1600
	Hydraulic System		Open	Open
	Hydraulic System Oil Pressure(MPa)		32	32
	Oil Tank Capacity(L)		320	320
	Water Tank Capacity(L)		700	700
	Pipe Diameter(mm)		125	125
	End Hose Length(m)		3	3
	End Hose Diameter(mm)		125	125
Chassis Specification	Chassis Brand		SINOTRUK	SINOTRUK
	Chassis Model		ZZ5235N521GC1	ZZ5235N5213C1R
	Engine Type		MC07.31-30	MC07.31-30
	Engine Maximum Net Power(kW/rpm)		225/2300	225/2300
	Emission Standard		China stage Ⅲ	China stage Ⅲ
	Fuel Tank Capacity(L)		300	300
	Displacement(L)		6.87	6.87
	Max. Speed(km/h)		90	90









